

loading bridge:	Aluminum trough made of 25 mm hollow profiles, front wall 25 mm thick with solid corner posts. 2-leaf rear portal, with two internal espagnolette locks per door leaf. 3 standard cross bows galvanized. Hydraulic moving floor system CARGO FLOOR with 21 moving floor boards 6 mm thick, grooved or smooth design. with hydraulic piping up to the bulkhead including standard screw coupling. Removable cross bow or end cross beam at the rear, front side access platform with access left or right in the direction of travel, broom holder and shovel holder on the front wall.
Execution for	Version 34 pallet spaces includes:
34 pallet spaces	• Inside length 13,620 mm • Moving end wall to be operated pneumatically or electrically by means of a cable winch
Lighting system:	According to STVO EC Directive 76/756/EEC 24 volts, ground-free, tail lights made of 9 chambers Europoint lights, with built-in flashing light, rear fog light and reversing light. Single-line license plate, 2 position lights each, mounted on a rubber arm at the rear, with white reflectors on the front, amber side marker lights, all position lights are based on LEDs.
Additionally:	6 pieces of PVC full-shell fenders with mudflaps, 1 piece PVC chock incl. holder, 1 piece PVC tool box, lateral collision protection made of anodised aluminum profiles, Aluminum underride guard coated white with protective flap for lights and long dirt traps, open spare wheel holder galvanized, COC documentation, 4 tension belts for roof roll-up tarpaulin, Roof roll-up tarpaulin, reinforced 900 g/m² with 2 or 1 integrated roof tubes and an aluminum batten on the left side of the vehicle for winding the tarpaulin, 4 pieces of tarpaulin stops on the right side, Revolving bulkhead with towing tarpaulin and special rail cleaner, Reflective contour marking strips according to ECE104.
Paint :	All steel parts granulated cleaned. Careful priming and spray painting with premium acrylic paint. Certified painting according to DIN 50017KK Certified paintwork.
Disclaimer:	All information without guarantee and subject to technical changes and typographical errors.